

Amendments to the Claims

The listing of claims set forth below replace all prior versions and listings in the present patent application:

Listing of Claims:

1. (Currently amended) A method for pre-heating a hydrocarbon catalytic reformer from a starting temperature to a minimum reforming temperature utilizing an electronic control module, comprising the steps of:
 - a) selecting a fuel type to be combusted;
 - b) determining the latent heat of combustion of said selected fuel type;
 - c) selecting a flow rate of said combustion fuel;
 - d) determining the heat capacity of the a catalyst to be heated in said catalytic reformer;
 - e) determining a mass of said reformer to be heated;
 - f) determining a starting temperature of said catalyst in said catalytic reformer;
 - g) utilizing a software construct to produce said fuel combustion time interval, wherein said construct utilizes said latent heat of combustion, said selected combustion fuel flow rate, said heat capacity of said catalyst, said mass to be heated, and said starting temperature; and
 - h) pre-heating said hydrocarbon catalytic reformer using a combustor for said fuel combustion time interval so that said hydrocarbon catalytic reformer reaches said minimum reforming temperature.

2. (Original) A method in accordance with Claim 1 wherein said software construct includes an algorithm, software code modules, or interface specifications.

3. (Original) A method in accordance with Claim 1 wherein said software construct is an algorithm having the linear form $y = mx + b$.

4. (Original) A method in accordance with Claim 3 wherein
y is said minimum reforming temperature;
b is said starting temperature;
m is an integral of a product of said latent heat of combustion times said selected flow rate of said combustion fuel, divided by a product of said mass to be heated times the heat capacity of said mass; and
x is said fuel combustion time interval.

5. (Original) A method in accordance with Claim 1 wherein said minimum reforming temperature is about 500°C.

6. (Currently amended) A catalytic hydrocarbon reformer for making reformat, comprising:

an electronic control module for controlling the flow of hydrocarbon fuel and air into said reformer,

wherein said electronic control module is programmed with a software construct for determining a fuel combustion time interval for pre-heating said hydrocarbon catalytic reformer ~~from a starting temperature~~ to a minimum reforming temperature, wherein said fuel combustion time interval is at least dependent on a starting temperature of a catalyst in said reformer.

7. (Previously presented) A catalytic hydrocarbon reformer in accordance with Claim 6 wherein said software construct includes an algorithm, software code modules, or interface specifications.

8. (Previously presented) A catalytic hydrocarbon reformer in accordance with Claim 6 wherein said software construct is an algorithm having the linear form $y = mx + b$, and wherein

y is said minimum reforming temperature;

b is said starting temperature;

m is an integral of a product of the latent heat of combustion of said fuel times the selected flow rate of said fuel, divided by a product of the mass of said reformer to be heated times the heat capacity of said mass; and

x is said fuel combustion time interval.

9. (Previously presented) A catalytic hydrocarbon reformer in accordance with Claim 6 wherein said fuel cell assembly includes a solid oxide fuel cell.

10. (Currently amended) A computing system having a processor, a memory and an operating environment operable to execute a method for determining a fuel combustion time interval for pre-heating a hydrocarbon catalytic reformer from a starting temperature to a minimum reforming temperature, the method comprising:

- a) selecting a fuel type to be combusted;
- b) determining the latent heat of combustion of said selected fuel type;
- c) selecting a flow rate of said combustion fuel;
- d) determining the heat capacity of ~~the~~ a catalyst to be heated in said catalytic reformer;

- e) determining a mass of said reformer to be heated;
- f) determining a starting temperature of said catalyst in said catalytic reformer;

and

- g) utilizing a software construct to produce said fuel combustion time interval, wherein said construct utilizes said latent heat of combustion, said selected combustion fuel flow rate, said heat capacity of said catalyst, said mass to be heated, and said starting temperature.

11. (Original) A computing system in accordance with Claim 10

wherein said software construct includes an algorithm, software code modules or interface specifications.

12. (Original) A computing system in accordance with Claim 10

wherein said software construct is an algorithm having the linear form $y = mx + b$.

13. (Original) A computing system in accordance with Claim 12

wherein

y is said minimum reforming temperature;

b is said starting temperature;

m is an integral of a product of said latent heat of combustion times said selected flow rate of said combustion fuel, divided by a product of said mass to be heated times the heat capacity of said mass; and

x is said fuel combustion time interval.

14. (Original) A computing system in accordance with Claim 10

wherein said minimum reforming temperature is about 500°C.

15. (Currently amended) A computer readable medium having computer executable instructions of a wired media type for performing a method for determining a fuel combustion time interval for pre-heating a hydrocarbon catalytic reformer from a starting temperature to a minimum reforming temperature, comprising the steps of:

- a) selecting a fuel type to be combusted;
- b) determining the latent heat of combustion of said selected fuel type;
- c) selecting a flow rate of said combustion fuel;
- d) determining the heat capacity of the a catalyst to be heated in said catalytic reformer;
- e) determining a mass of said reformer to be heated;
- f) determining a starting temperature of said catalyst in said catalytic reformer;

and

- g) utilizing a software construct to produce said fuel combustion time interval,

wherein said construct utilizes said latent heat of combustion, said selected combustion fuel flow rate, said heat capacity of said catalyst, said mass to be heated, and said starting temperature.

16. (Original) A computer readable medium in accordance with Claim 15 wherein said software construct includes an algorithm, software code modules or interface specifications.

17. (Original) A computer readable medium in accordance with Claim 15 wherein said software construct is an algorithm of the linear form $y = mx + b$.

18. (Original) A computer readable medium in accordance with Claim 17 wherein

y is said minimum reforming temperature;

b is said starting temperature;

m is an integral of the product of said latent heat of combustion times said selected flow rate of said combustion fuel, divided by a product of said mass to be heated times the heat capacity of said mass; and

x is said fuel combustion time interval.

19. (Original) A computer readable medium in accordance with Claim 15 wherein said minimum reforming temperature is about 500°C.